





ELITECH LINE

Premium Range Hood Type Dishwasher - 500 x 500



EL60E

The Krupps ELITECH EL60E pass-through dishwasher is the top of the range thanks to its new construction technologies which guarantees highly efficient and effective results time and time again.

The **EL60E** is the right solution for businesses that are faced with the washing of different types of dishes, proving capable of washing glasses, dishes, medium sized objects up to 500x500x390(h) mm and GN1/1 container, ensuring a maximum productivity of **1080 dishes/hour** or **2160 glasses/hour**.

Water consumption is guaranteed to an amazing 2 litres per cycle, regardless of the wash cycle time. The Thermo-stop function ensures that the washing and rinsing only starts when the desire temperature is reached.

The standard **double peristaltic electric rinse-aid and detergent dispenser** ensures the best result from each wash cycle with great savings thanks to the precise dosage.

The dishwashers of the **ELITECH** line ensure maximum performance thanks to the standard **Acquatech System** which, through an **atmospheric boiler and rinse pump**, maintains constant temperature and pressure and optimum water consumption. ELITECH ensures a **sanitising rinse cycle** and proves to be the perfect choice for every kitchen where compliance with HACCP rules is essential.

The **innovative UNIKO tempered glass touch screen** display makes any operation simple and intuitive, from the choice of the most suitable wash cycle to its progress control, as well as constantly monitoring the status of the dishwasher with ease. The choice of **4 wash cycles** makes the dishwasher customisable according to your needs. The integrated **self-diagnosis minimises machine downtime** advising you of any problems encountered.

The "PUSH TO START" cycle start system ensures less waste; preventing the start of empty washes.

The **self-cleaning cycle** at the end of the day cleans the wash tank and empties the boiler from the hot water, preventing limestone forming inside. Six rinse cycles will then start to sanitize the washing chamber. When completed, the water from rinsing is drained completely to avoid bacteria proliferation.

Stainless steel moulded washing and rinsing arms ensure great reliability and durability. The bodywork is made entirely of AISI 304 stainless steel and has been designed with all components in the front for easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

Optional: Wi-Fi IKLOUD control system that offers the possibility of remotely changing the dishwasher parameters and being monitored by your favourite service provider.

Complete with built in drain, rinse, detergent and rinse aid pumps and backflow prevention by break-tank.

Comes with one glass rack 500x500x100mm, two 18-plate dish racks 500x500x100mm, one 8-division cutlery container and two integral tank filters.









ELITECH LINE

Premium Range Hood Type Dishwasher







6.74kW 400V/3Ph - 230V/1Ph L= 1900mm



G3/4" M L= 1200mm



Ø25x30 L=1550mm

FEATURES	EL60E
Dimensions - WxDxH (mm)	620x770x1435/1900
Rack dimensions (mm)	500 x 500
Productivity per hour max - (+55°C)	1080 dishes/hour 2160 glasses/hour
Height glass max	390mm
Ø Height plate max	415mm
Trays	GN1/1
Body construction	Entirely AISI304 stainless steel
Rinsing and washing arms	Ø30 stainless steel - upper/ lower separated
Stainless steel filters	Yes
Tank heating element - Tank capacity	4.5kW - 37lt
Boiler heating element - Boiler capacity	5.4kW - 7.3lt
Washing pump power	1.34kW
Total power input / Current	6.74kW
Input voltage	400V/2Ph - 230V/1Ph
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet sug- gested pressure 2 BAR)	2,0lt GUARANTEED
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Acquatech system rinse	250W
Drain pump	190W
Rinse pump	Yes
Rinse cycle on demand	Yes
Energy - Saving device	Yes
Backflow prevention	Break-tank
Control panel	UNIKO touch glass display
Washing cycles	4 - 90/110/120/300 sec or customized timing
Self-diagnostic system	Yes
Self-cleaning cycle	Yes
Supplied with	2 x integral tank filter, 1 x 8 division cutlery container,